

Manual Call Point

- Available for flush or surface mounting.
- Plastic film on glass.
- Test key inserted from bottom.
- Open circuit with series resistor.
- Suitable for the majority of conventional fire alarm system

Model	: S-330
Max.Voltage	: 50VDC
Min.Voltage	: 2V
Max.Current	: 1A
Resistance	: 0.15 Ohms
Power Rating	: 1W
Temperature	: -40 ° C ~ + 85 ° C



S-330

Manual Pull Point



S-334

Model	: S-334
Application	: Indoor
Adopted voltage	: DC ~ 18 ~ 28V (DC-24)
Adopted current	: 100 mA
Function	: Push Button Emergency,Phone Jack, Reset Switch,confirmation LED lamp
Color	: Red
Size	: 138 mm x 48 mm
Weight	: 150 g
Joint volume	: DC - 30V 1A

Fire Alarm Bell 6"



S-332

Model	: S-332
Voltage	: 24V DC
Current	: 25 mA
Sound Output	: 93dBA@ 1M
Movement	: Motor, Pinion and Striker
Movement Features	: DC motor, acetral gear wheel steel striker
Gong	: Steel, secured with phillips screw
Base Plate	: Molded black polycarbonate
Dimension / Weight	: 6 " (152 mm) / 0.85 kg

Flash Lamp

Model	: S-350
Power Source	: 24V DC
Standby Current	: 24V DC 12mA
Operating Current	: 160 mA
Ambient Temperature	: -10 °C ~+ 55 °C
Relative Humidity	: 10 ~ 95%
Material	: Fire-proof plastic
Color	: White



S-350